

# Callback API 0.2 [beta] (eng. version)

The **Callback API** is used for receiving events and controlling the callback widget on your website.

 Mail for your questions: [support@onlinepbx.ru](mailto:support@onlinepbx.ru).

## Contents

[Connection and setup](#)

[Controlling the widget](#)

[Widget events](#)

---

## Connection and setup

```
<script type="text/javascript" src="https://callback.onlinepbx.ru/loader.js" charset="UTF-8" data-onpbxcb-id="ID WIDGET"></script>
```

## Data attributes

Attribute	Note	Description
data-onpbxcb-id	mandatory	Widget ID
data-dest		Destination number (the call will be made from a different number on this page)

Example:

```
data-onpbxcb-id = Widget ID  
data-dest = Destination number
```

 Widget ID is located in the callback widget code, on the [settings page](#) onlinePBX.

---


## Controlling the widget

Object	Description
OnlinePBXWebWidget.expand()	Force widget to expand, displaying number input form
OnlinePBXWebWidget.collapse()	Force widget to collapse deplo widget
OnlinePBXWebWidget.disable()	Hide and disable widget
OnlinePBXWebWidget.destroy()	Remove widget code from page

[To contents](#)

---

## Widget events

 Located after loader:

---

```

<script type="text/javascript">
Initialization
if (typeof OnlinePBXWebWidget == 'undefined')
OnlinePBXWebWidget = {events:{}};
Triggered when widget completes initialization
OnlinePBXWebWidget.events.init = function() {
};
Triggered when user clicks button
OnlinePBXWebWidget.events.expandclick = function() {
};
Triggered when form deploys
OnlinePBXWebWidget.events.expandauto = function() {
};
Triggered when user clicks the cross in the upper right corner of window
@param {String} src - source (hunter - automatically opens form when clicked)

OnlinePBXWebWidget.events.disableclick = function(src) {
};

Triggered when user has entered number in form and clicks "receive call"
@param {String} number
@param {String} src - source (hunter - automatically opens form when clicked)

OnlinePBXWebWidget.events.callrequest = function(number, src) {

// yaCounter123456.reachGoal('goalname');
};

Triggered by successful call
@param {String} number
@param {String} op - name of operator
@param {String} src - source (hunter - automatically opens form when clicked)

OnlinePBXWebWidget.events.callsuccess = function(number, op, src) {
};
Triggered if user has requested a call, but we are unable to make it.
@param {String} number
@param {String} error - text of error message
@param {String} src - source (hunter - automatically opens form when clicked)

OnlinePBXWebWidget.events.callfail = function(number, error, src) {
};
</script>

```

[To contents](#)